

Technical Data:					
	Basket [Ø/H/loading] [mm/mm/kg]	Rotational Speed [min-1]	Heating Capacity [kW]	Voltage [V/Hz]	Dimensions W x D x H [mm]
TZ 5	180/120/2	550-1400	0,8	230/50	470x400x580
TZ 10	270/190/5	700-1100	2,1	230/50	700x500x950
TZ 25	380/250/15	500-800	4,1	400/50	710x690x1100
TZ 30	220/180/10	500-1400	1,3	230/50	475 x 630 x 915
TZ 100	430/280/50	300-1000	3	400/50	670 x 900 x 1035



Deburring - Rounding - Grinding - Smoothing - Polishing



**C**entrifugal dryer  
for spotless drying of workpieces after vibratory finishing

## Centrifugal Dryer TZ 5, TZ 10 and TZ 25

for drying bulk goods

- solid centrifuge housing made of steel sheet
- cover and water-bearing areas in stainless steel
- mesh feet, height-adjustable, vibration-reducing and fixable
- rotor for holding baskets
- variable speed control
- thermostatically adjustable hot air temperature
- safety lock of the centrifuge cover
- time switch 1 - 60 min
- filter bags



Bulk materials as well as sensitive parts can be dried in the centrifugal dryer  
Special versions of baskets, sieves and adapter on request

## Centrifugal Dryer TZ 30 and TZ 100

for drying bulk goods, especially for sensitive workpieces

- case made of durable coated steel with lid of stainless steel and service cover on the front side (no attachment on the floor required)
- rotor for the accommodation of baskets
- adjustable rotation speed
- thermostatic regulation of temperature
- electronic standstill surveillance
- safety lock of centrifuge lid
- timer



larger centrifugal dryers on request